NSN 5306-01-057-6684

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-057-6684

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.413 inches
Fastener Length:
Between 1.548 inches and 1.578 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Hole Diameter:
0.075 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response

NSN 5306-01-057-6684

Shear Bolt - Page 2 of 2



Thread Series Designator:

Unjf

Specification Data:

80205-nas6205 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.