

View Online at <https://aerobasegroup.com/nsn/5306-01-057-7210>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.438 inches and 0.468 inches

**Fastener Length:**

Between 5.188 inches and 5.218 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.250 inches and 0.265 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

4.750 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

33.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.065 inches first hole and 5.095 inches first hole

**Material:**

Steel comp e4340

**Surface Treatment:**

Cadmium head

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0