## NSN 5306-01-058-0734

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-058-0734

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.163 inches and 1.213 inches **Fastener Length:** Between 3.923 inches and 3.953 inches **Head Style:** Spline extended washer **Head Height:** Between 0.472 inches and 0.512 inches **Extended Washer Diameter:** Between 1.384 inches and 1.394 inches **Extended Washer Thickness:** Between 0.098 inches and 0.118 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches **Head Minor Diameter:** Between 0.904 inches and 0.912 inches **Thread Diameter:** 0.750 inches **Grip Length:** Between 2.740 inches and 2.760 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5306-01-058-0734

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: