## NSN 5306-01-058-3327

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-058-3327

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.828 inches and 0.878 inches **Fastener Length:** Between 2.088 inches and 2.118 inches **Head Style:** Spline extended washer **Head Height:** Between 0.358 inches and 0.398 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Head Minor Diameter:** Between 0.644 inches and 0.651 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5306-01-058-3327

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: