NSN 5306-01-058-3892

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-058-3892

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.925 inches and 0.975 inches **Fastener Length:** Between 2.935 inches and 2.965 inches **Head Style:** Spline extended washer **Head Height:** Between 0.040 inches and 0.444 inches **Extended Washer Diameter:** Between 1.037 inches and 1.047 inches **Extended Washer Thickness:** Between 0.071 inches and 0.091 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Head Minor Diameter:** Between 0.711 inches and 0.717 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.990 inches and 2.010 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response

Unjf

Thread Series Designator:

NSN 5306-01-058-3892

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
V003P0

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: