

View Online at <https://aerobasegroup.com/nsn/5306-01-058-3911>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.968 inches and 1.018 inches

Fastener Length:

Between 3.103 inches and 3.133 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.701 inches and 0.721 inches

Width Between Flats:

Between 0.808 inches and 0.817 inches

Extended Washer Diameter:

Between 1.220 inches and 1.230 inches

Extended Washer Thickness:

Between 0.168 inches and 0.188 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 2.115 inches and 2.135 inches

Thread Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735

Surface Treatment:

Cadmium

Thread Series Designator:

Unjf

Specification Data:

80205-nas632 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0