

View Online at <https://aerobasegroup.com/nsn/5306-01-059-1086>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.500 inches

Fastener Length:

Between 5.400 inches and 5.560 inches

Head Style:

Button

Head Diameter:

Between 1.219 inches and 1.344 inches

Head Height:

Between 0.313 inches and 0.344 inches

Neck Length:

Between 0.313 inches and 0.344 inches

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

11

Min. Tensile Strength (psi):

60000 pounds per square inch

Neck Width:

Between 0.616 inches and 0.642 inches

Material:

Steel

Material Specification:

Astm a307, gr a assn standard single material response or ff-b-584, gr 1 federal specification single material response

Surface Treatment:

Cadmium and chromate or zinc and chromate or cadmium or zinc

Surface Treatment Specification:

Qq-p-416, cl 3 federal specification 1st treatment response and qq-p-416, cl 3 federal specification 2nd treatment response or qq-z-325, cl 3 federal specification 3rd treatment response and qq-z-325, cl 3 federal specification 4th treatment response or mil-c-81562, type 2, cl 3 military specification 5th treatment response or mil-c-81562, type 2, cl 3 military specification 6th treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 1 class and a style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.