NSN 5306-01-059-1947

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-059-1947

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.709 inches and 0.759 inches **Fastener Length:** Between 1.719 inches and 1.749 inches **Head Style:** Spline extended washer **Head Height:** Between 0.263 inches and 0.303 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Head Minor Diameter:** Between 0.448 inches and 0.455 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response

Thread Series Designator: Unjf

NSN 5306-01-059-1947

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: