
## NSN 5306-01-059-2654

Shear Bolt - Page 1 of 2





#### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.298 inches and 0.348 inches

## Fastener Length:

Between 1.496 inches and 1.526 inches

#### Head Style:

Dished hexagon

## Head Height:

Between 0.110 inches and 0.125 inches

## Width Between Flats:

Between 0.367 inches and 0.376 inches

### Grip Diameter:

Between 0.1885 inches and 0.1895 inches

## Thread Diameter:

0.190 inches

## Grip Length:

Between 1.178 inches and 1.198 inches

## Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

#### Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas6203 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-059-2654

Shear Bolt - Page 2 of 2

Fiig: A003b0

