NSN 5306-01-059-3587

Close Tolerance Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-059-3587

View Online at https://aerobasegroup.com/nsn/5306-01-059-3587
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.444 inches and 0.494 inches
Fastener Length:
Between 3.079 inches and 3.109 inches
Head Style:
Undercut hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 2.615 inches and 2.635 inches
Thready Qty Per Inch (tpi):
24
24
24 Surface Finish:
24 Surface Finish: 32.0 microinches threads
24 Surface Finish: 32.0 microinches threads Material:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf Shelf Life:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf Shelf Life:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unjf Shelf Life:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure:
24 Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qaq-p-416, type 2, class 3 federal specification single treatment response Mread Series Designator: Unjf Shelf Life: N/a Lifo Measure: Demilitarization: No