# NSN 5306-01-059-5914

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-059-5914



Thread Class:

3a

**Thread Direction:** 

Right-hand

Thread Length:

Between 0.823 inches and 0.873 inches

#### Fastener Length:

Between 1.833 inches and 1.863 inches

#### Head Style:

Spline extended washer

#### Head Height:

Between 0.310 inches and 0.350 inches

#### **Extended Washer Diameter:**

Between 0.807 inches and 0.817 inches

#### **Extended Washer Thickness:**

Between 0.053 inches and 0.073 inches

#### **Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

#### Head Minor Diameter:

Between 0.514 inches and 0.521 inches

### Thread Diameter:

0.438 inches

Grip Length:

Between 0.990 inches and 1.010 inches

#### Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

260000 pounds per square inch

#### Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

#### Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

#### **Material Specification:**

Ams 6487 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

#### **Thread Series Designator:**

Unjf

# NSN 5306-01-059-5914

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-c-8837 spec.

