## NSN 5306-01-059-7458

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-059-7458

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.474 inches and 0.541 inches
Fastener Length:
Between 2.109 inches and 2.156 inches
Head Style:
Hexagon
Head Height:
Between 0.296 inches and 0.328 inches
Width Between Flats:
Between 0.928 inches and 0.940 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
Single Shear Strength:
29150 pounds per square inch
Thread Diameter:
0.625 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas464 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-059-7458

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0