

View Online at <https://aerobasegroup.com/nsn/5306-01-060-1409>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.444 inches

Fastener Length:

Between 1.454 inches and 1.474 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

Width Between Flats:

Between 0.367 inches and 0.377 inches

Shoulder Diameter:

0.249 inches first shoulder

Shoulder Length:

1.010 inches first shoulder and 1.030 inches first shoulder

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.304 inches first hole and 1.644 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Dry film lube on grip only

Material:

Steel

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0