

View Online at <https://aerobasegroup.com/nsn/5306-01-060-6842>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.454 inches

Fastener Length:

Between 1.694 inches and 1.714 inches

Head Style:

Spline drive shear head

Head Height:

0.210 inches

Grip Diameter:

Between 0.3733 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Head Minor Diameter:

0.679 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.482 inches first hole and 1.502 inches first hole

Special Features:

Dry film lube per mil-I-8937b on bearing surface of head and grip

Material:

Stainless steel

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium top of head

Surface Treatment Specification:

Nas672 national specification single treatment response top of head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0