

View Online at <https://aerobasegroup.com/nsn/5306-01-060-6842>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.454 inches

**Fastener Length:**

Between 1.694 inches and 1.714 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.210 inches

**Grip Diameter:**

Between 0.3733 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Head Minor Diameter:**

0.679 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.240 inches and 1.260 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.482 inches first hole and 1.502 inches first hole

**Special Features:**

Dry film lube per mil-I-8937b on bearing surface of head and grip

**Material:**

Stainless steel

**Material Specification:**

Ams6487 assn standard single material response

**Surface Treatment:**

Cadmium top of head

**Surface Treatment Specification:**

Nas672 national specification single treatment response top of head

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0