

View Online at <https://aerobasegroup.com/nsn/5306-01-060-6843>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

Between 2.080 inches and 2.100 inches

Head Style:

Spline drive shear head

Head Height:

0.281 inches

Width Between Flats:

0.901 inches

Grip Diameter:

Between 0.4982 inches and 0.4991 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.825 inches first hole and 1.845 inches first hole

Special Features:

Dry film lube per mil-I-8937b on bearing surface of head and grip

Material:

Stainless steel

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium top of head

Surface Treatment Specification:

Nas672 national specification single treatment response top of head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0