

View Online at <https://aerobasegroup.com/nsn/5306-01-060-6843>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.528 inches

**Fastener Length:**

Between 2.080 inches and 2.100 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.281 inches

**Width Between Flats:**

0.901 inches

**Grip Diameter:**

Between 0.4982 inches and 0.4991 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.552 inches and 1.572 inches

**Thread Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.825 inches first hole and 1.845 inches first hole

**Special Features:**

Dry film lube per mil-I-8937b on bearing surface of head and grip

**Material:**

Stainless steel

**Material Specification:**

Ams6487 assn standard single material response

**Surface Treatment:**

Cadmium top of head

**Surface Treatment Specification:**

Nas672 national specification single treatment response top of head

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0