

View Online at <https://aerobasegroup.com/nsn/5306-01-060-7240>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.444 inches

**Fastener Length:**

Between 1.484 inches and 1.504 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.109 inches and 0.141 inches

**Width Between Flats:**

Between 0.367 inches and 0.377 inches

**Shoulder Diameter:**

0.248 inches first shoulder and 0.249 inches first shoulder

**Shoulder Length:**

1.040 inches first shoulder and 1.060 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.334 inches first hole and 1.354 inches first hole

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Dry film lube per mil-I-46010 on grip only

**Material:**

Steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0