

View Online at <https://aerobasegroup.com/nsn/5306-01-060-7244>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 1.365 inches and 1.385 inches

Head Style:

Hexagon

Head Height:

Between 0.172 inches and 0.204 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Shoulder Diameter:

0.374 inches first shoulder

Shoulder Length:

0.990 inches first shoulder and 1.010 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.205 inches first hole and 1.225 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Dry film lube per mil-I-46010 on grip only

Material:

Steel

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Nas 672 assn standard single treatment response threads

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0