NSN 5306-01-061-1957

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-061-1957 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.395 inches **Fastener Length:** Between 0.543 inches and 0.573 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Special Features:** Pellet-type or strip-type or patch-type element on threads Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6204 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-061-1957

Shear Bolt - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0