

View Online at <https://aerobasegroup.com/nsn/5306-01-061-8344>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.444 inches

Fastener Length:

Between 2.559 inches and 2.579 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

Width Between Flats:

Between 0.367 inches and 0.377 inches

Shoulder Diameter:

0.249 inches first shoulder and 0.250 inches first shoulder

Shoulder Length:

2.115 inches first shoulder and 2.135 inches first shoulder

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.409 inches first hole and 2.429 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Dry film lube per mil-I-46010 on grip only

Material:

Steel

Material Specification:

Ams6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Nas 672 assn standard single treatment response threads

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0