NSN 5306-01-062-1049

Shear Bolt - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-062-1049

| Right-hand |
|--|
| Thread Length: |
| Between 0.413 inches and 0.463 inches |
| Fastener Length: |
| Between 0.485 inches and 0.515 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.156 inches and 0.171 inches |
| Width Between Flats: |
| Between 0.492 inches and 0.502 inches |
| Hole Diameter: |
| 0.075 inches |
| Grip Diameter: |
| Between 0.3115 inches and 0.3120 inches |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.052 inches and 0.072 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon flats |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas6305 professional/industrial association standard |
| |
| |

NSN 5306-01-062-1049

Shear Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0