## NSN 5306-01-063-1000

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-063-1000

View Online at https://aerobasegroup.com/nsn/5306-01-063-1000
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.650 inches and 1.690 inches
Fastener Length:
Between 2.785 inches and 2.805 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 1.041 inches and 1.061 inches
Width Between Flats:
Between 1.240 inches and 1.260 inches
Extended Washer Diameter:
Between 1.865 inches and 1.875 inches
Extended Washer Thickness:
Between 0.248 inches and 0.268 inches
Grip Diameter:
Between 1.1225 inches and 1.1240 inches
Thread Diameter:
1.125 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-063-1000

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0