

View Online at <https://aerobasegroup.com/nsn/5306-01-063-2346>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.625 inches and 0.685 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.258 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

0.375 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**First Diameter From Head:**

Between 0.165 inches and 0.175 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.065 inches and 0.125 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Minimum Yield Strength:**

107000 pounds per square inch

**Special Features:**

Solid film lube with everlube 620or lube-lok 5396 per hs248 ty a1 cl 43

**Material:**

Steel

**Material Specification:**

Ams 5731 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0