

View Online at <https://aerobasegroup.com/nsn/5306-01-064-3600>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.601 inches and 0.651 inches

Fastener Length:

Between 2.299 inches and 2.329 inches

Head Style:

Dished hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 1.678 inches and 1.698 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.082 inches first hole and 2.132 inches first hole

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6210 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0