

View Online at <https://aerobasegroup.com/nsn/5306-01-064-3602>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.966 inches and 1.033 inches

**Fastener Length:**

Between 3.288 inches and 3.335 inches

**Head Style:**

Double hexagon

**Head Height:**

0.468 inches

**Width Between Flats:**

Between 1.239 inches and 1.252 inches

**Grip Diameter:**

Between 0.8730 inches and 0.8740 inches

**Shank Unthreaded Hole Diameter:**

0.136 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 2.302 inches and 2.322 inches

**Thread Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.164 inches first hole and 3.176 inches first hole

**Material:**

Steel comp h11

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0