

View Online at <https://aerobasegroup.com/nsn/5306-01-064-6264>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.618 inches and 0.668 inches

Fastener Length:

Between 1.878 inches and 1.908 inches

Head Style:

Spline extended washer

Head Height:

Between 0.302 inches and 0.322 inches

Width Between Flats:

Between 0.383 inches and 0.389 inches

Extended Washer Diameter:

Between 0.521 inches and 0.531 inches

Extended Washer Thickness:

Between 0.051 inches and 0.071 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Head Minor Diameter:

Between 0.383 inches and 0.389 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Special Features:

Paint color white

Material:

Steel comp 8740 or steel comp 4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 1 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.