

View Online at <https://aerobasegroup.com/nsn/5306-01-064-7458>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.475 inches and 0.525 inches

**Fastener Length:**

2.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.312 inches and 0.327 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 1.678 inches and 1.698 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.914 inches first hole and 1.964 inches first hole

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0