NSN 5306-01-065-6797

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-065-6797 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.760 inches and 0.880 inches **Fastener Length:** Between 2.000 inches and 2.060 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.124 inches and 0.151 inches Width Between Flats: Between 0.305 inches and 0.312 inches **Extended Washer Diameter:** Between 0.384 inches and 0.414 inches **Extended Washer Thickness:** Between 0.019 inches and 0.031 inches Point Length: 0.200 inches **Point Diameter:** Between 0.130 inches and 0.135 inches First Diameter From Head: Between 0.180 inches and 0.190 inches **Second Diameter From Head:** Between 0.130 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.120 inches and 1.270 inches Point Style: Dog **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 28.0 rockwell c and 34.0 rockwell c **Externally Relieved Body Diameter Quantity:**

1

Material:

Steel

NSN 5306-01-065-6797

Externally Relieved Body Bolt - Page 2 of 2



Surface Treatment:
Zinc
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0