

View Online at <https://aerobasegroup.com/nsn/5306-01-065-6797>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.760 inches and 0.880 inches

**Fastener Length:**

Between 2.000 inches and 2.060 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

Between 0.124 inches and 0.151 inches

**Width Between Flats:**

Between 0.305 inches and 0.312 inches

**Extended Washer Diameter:**

Between 0.384 inches and 0.414 inches

**Extended Washer Thickness:**

Between 0.019 inches and 0.031 inches

**Point Length:**

0.200 inches

**Point Diameter:**

Between 0.130 inches and 0.135 inches

**First Diameter From Head:**

Between 0.180 inches and 0.190 inches

**Second Diameter From Head:**

Between 0.130 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.170 inches and 0.190 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.120 inches and 1.270 inches

**Point Style:**

Dog

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

28.0 rockwell c and 34.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel

**Surface Treatment:**

Zinc

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0