NSN 5306-01-066-2454

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-066-2454 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.620 inches and 0.700 inches **Fastener Length:** Between 0.928 inches and 0.948 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches **End Application:** Spec item **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.248 inches and 0.308 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 42.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Titanium alloy **Material Specification:** Ams 4967 assn standard single material response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-066-2454 Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

Demilitarization:

No

Fiig:

A003b0