## NSN 5306-01-066-2469

View Online at https://aerobasegroup.com/nsn/5306-01-066-2469

Shear Bolt - Page 1 of 2





Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.345 inches and 0.395 inches

#### Fastener Length:

Between 0.855 inches and 0.885 inches

#### Head Style:

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

## Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Grip Diameter:

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:** 

0.250 inches

## Grip Length:

Between 0.490 inches and 0.510 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Titanium alloy

## Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas6404 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5306-01-066-2469

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

