

View Online at <https://aerobasegroup.com/nsn/5306-01-067-3388>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.390 inches and 0.468 inches

Fastener Length:

Between 1.468 inches and 1.515 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.615 inches and 0.627 inches

Grip Diameter:

Between 0.4358 inches and 0.4367 inches

Shank Unthreaded Hole Diameter:

0.096 inches first hole and 0.116 inches first hole

Thread Diameter:

0.438 inches

Grip Length:

Between 1.047 inches and 1.078 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.265 inches first hole and 1.297 inches first hole

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas464 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0