

View Online at <https://aerobasegroup.com/nsn/5306-01-067-3902>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.656 inches and 0.672 inches

Fastener Length:

Between 3.953 inches and 4.000 inches

Head Style:

Hexagon

Head Height:

Between 0.234 inches and 0.266 inches

Width Between Flats:

Between 0.615 inches and 0.627 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 3.297 inches and 3.328 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Material:

Aluminum alloy

Material Specification:

Qq-a-200 federal specification all material responses or qq-a-250 federal specification all material responses or qq-a-430 federal specification all material responses

Surface Treatment:

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Thread Series Designator:

Unf

Specification Data:

88044-an7 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-a-8625 spec.