NSN 5306-01-067-5173

U Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-067-5173

2a Thread Direction: Right-hand Thread Length: 0.840 inches Distance From Inside Center Of Bend To Bolt End: 2.285 inches Inside Distance Between Shanks: 1.630 inches Thread Diameter: 0.250 inches
Right-handThread Length:0.840 inchesDistance From Inside Center Of Bend To Bolt End:2.285 inchesInside Distance Between Shanks:1.630 inchesThread Diameter:
Thread Length: 0.840 inches Distance From Inside Center Of Bend To Bolt End: 2.285 inches Inside Distance Between Shanks: 1.630 inches Thread Diameter:
0.840 inches Distance From Inside Center Of Bend To Bolt End: 2.285 inches Inside Distance Between Shanks: 1.630 inches Thread Diameter:
Distance From Inside Center Of Bend To Bolt End: 2.285 inches Inside Distance Between Shanks: 1.630 inches Thread Diameter:
2.285 inches Inside Distance Between Shanks: 1.630 inches Thread Diameter:
Inside Distance Between Shanks: 1.630 inches Thread Diameter:
1.630 inches Thread Diameter:
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Material:
Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1020
Material Specification:
Astm a108 assn standard all material responses
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 ty1 cl1 federal specification single treatment response
Style Designator:
Round bend
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0