NSN 5306-01-069-0512

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-069-0512
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.387 inches and 0.437 inches
Fastener Length:
Between 1.335 inches and 1.365 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.310 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
Between 0.059 inches and 0.079 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:

Unjf

NSN 5306-01-069-0512

Shear Bolt - Page 2 of 2



	She	lf	Life:	
--	-----	----	-------	--

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0