NSN 5306-01-069-1542

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-069-1542 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.579 inches and 0.629 inches **Fastener Length:** Between 1.527 inches and 1.557 inches **Head Style:** Spline extended washer **Head Height:** Between 0.247 inches and 0.287 inches Width Between Flats: Between 0.360 inches and 0.375 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.035 inches and 0.055 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Surface Finish: 32.0 microinches grip Material: Steel **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837 ty2 class 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-069-1542

Close Tolerance Bolt - Page 2 of 2



	In	i+	∩f	RA.	~~	cii	re:
u	,,,	Iι	vı	IVI	ca.	่อน	ıe.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.