NSN 5306-01-070-1330

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-070-1330 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.625 inches and 0.685 inches **Fastener Length:** 3.500 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **First Diameter From Head:** Between 0.180 inches and 0.185 inches **Third Diameter From Head:** Between 0.180 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.210 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.312 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 1.542 inches and 1.582 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Between 2.815 inches and 2.875 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Steel

Material Specification:

Ams6322 assn standard single material response

NSN 5306-01-070-1330

Externally Relieved Body Bolt - Page 2 of 2



Surface Treatment:
Cadmium
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0