## NSN 5306-01-070-1712



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-070-1712 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 0.766 inches and 0.796 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Copper alloy 172 or copper alloy 173 or nickel alloy k-500 **Material Specification:** Qq-c-530 temper a federal specification 1st material response or qq-c-530 temper a federal specification 2nd material response or qq-n-286 federal specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1 cl 3 federal specification single treatment response **Thread Series Designator:** 

Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Unf

## NSN 5306-01-070-1712

Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0