

View Online at <https://aerobasegroup.com/nsn/5306-01-072-3247>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

2.430 inches

Head Style:

Fillister

Head Diameter:

Between 0.457 inches and 0.469 inches

Head Height:

Between 0.306 inches and 0.312 inches

First Diameter From Head:

Between 0.305 inches and 0.312 inches

Second Diameter From Head:

Between 0.250 inches and 0.260 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.193 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.490 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

Between 0.250 inches and 0.253 inches

Thready Qty Per Inch (tpi):

24

Externally Relieved Body Diameter Quantity:

2

Material:

Stainless steel

Surface Treatment:

Passivate and oxide

Surface Treatment Specification:

Qq-p-35, f-16 method 1 federal specification single treatment response and mil-c-13924, cl 4 f-33 method 2 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.