

View Online at <https://aerobasegroup.com/nsn/5306-01-074-3666>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.370 inches and 0.390 inches

Fastener Length:

Between 4.310 inches and 4.330 inches

Head Style:

Hexagon

Head Height:

Between 0.230 inches and 0.260 inches

Width Between Flats:

Between 0.428 inches and 0.440 inches

Hole Diameter:

Between 0.083 inches and 0.103 inches

First Diameter From Head:

Between 0.240 inches and 0.250 inches

Second Diameter From Head:

Between 0.205 inches and 0.210 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.090 inches and 0.110 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

3.940 inches

Thread Diameter:

0.250 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

5400 pounds per square inch

Hardness Rating:

34.0 rockwell c and 44.0 rockwell c

Hole Configuration Style:

Hexagon flats

Externally Relieved Body Diameter Quantity:

1

Special Features:

No.2 combination center drill, csk58-62 degrees to 0.150-0.170 inches, optional, both ends

Material:

Nickel alloy

Material Specification:

Ams 5708 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0