

View Online at <https://aerobasegroup.com/nsn/5306-01-074-3666>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.370 inches and 0.390 inches

**Fastener Length:**

Between 4.310 inches and 4.330 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.230 inches and 0.260 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Hole Diameter:**

Between 0.083 inches and 0.103 inches

**First Diameter From Head:**

Between 0.240 inches and 0.250 inches

**Second Diameter From Head:**

Between 0.205 inches and 0.210 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.090 inches and 0.110 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

3.940 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

5400 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 44.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

No.2 combination center drill, csk58-62 degrees to 0.150-0.170 inches, optional, both ends

**Material:**

Nickel alloy

**Material Specification:**

Ams 5708 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0