Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-074-4466

2a Thread Direction: Right-hand Thread Length: 0.688 inches Fastener Length: 2.000 inches Head Style: Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Head Height: Between 0.736 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Oty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
Right-handThread Length:0.688 inchesFastener Length:2.000 inchesHead Style:Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesFirst Diameter From Head:Between 0.410 inches and 0.420 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.500 inchesThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Externally Relieved Body Diameter Quantity:1Material:
Thread Length:0.688 inchesFastener Length:2.000 inchesHead Style:Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesFirst Diameter From Head:Between 0.410 inches and 0.420 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:1.312 inchesThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Externally Relieved Body Diameter Quantity:1Material:
0.688 inches Fastener Length: 2.000 inches Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1
Fastener Length:2.000 inchesHead Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesFirst Diameter From Head:Between 0.410 inches and 0.420 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:1.312 inchesThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Externally Relieved Body Diameter Quantity:1Material:
2.000 inches Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1
Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesBetween 0.736 inches and 0.750 inchesFirst Diameter From Head:Between 0.410 inches and 0.420 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:1.312 inchesThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Externally Relieved Body Diameter Quantity:11
Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
Head Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesFirst Diameter From Head:Between 0.410 inches and 0.420 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:1.312 inchesThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Externally Relieved Body Diameter Quantity:1Material:
Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
Width Between Flats: Between 0.736 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
Between 0.736 inches and 0.750 inches First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
First Diameter From Head: Between 0.410 inches and 0.420 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
Between 0.410 inches and 0.420 inches <b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b> 1.312 inches <b>Thread Diameter:</b> 0.500 inches <b>Thready Qty Per Inch (tpi):</b> 13 <b>Externally Relieved Body Diameter Quantity:</b> 1 <b>Material:</b>
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
1.312 inches Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
0.500 inches Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
Thready Qty Per Inch (tpi): 13 Externally Relieved Body Diameter Quantity: 1 Material:
13 Externally Relieved Body Diameter Quantity: 1 Material:
Externally Relieved Body Diameter Quantity: 1 Material:
1 Material:
Material:
Stainless steel
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0