

View Online at <https://aerobasegroup.com/nsn/5306-01-074-7413>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.385 inches

Fastener Length:

2.155 inches

Head Style:

Crowned hexagon

Head Height:

0.160 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Shoulder Diameter:

0.498 inches first shoulder and 0.499 inches first shoulder

Shoulder Length:

1.770 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.035 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Coat top and sides of head with one coat epoxy primer per mil-p-23377 and two coats urethane mil-c-83286 color no. 17875 white

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 cond e4 or cond c4 military specification single material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 2nd treatment response threads

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.