

View Online at <https://aerobasegroup.com/nsn/5306-01-076-4756>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.437 inches

Fastener Length:

Between 1.390 inches and 1.450 inches

Head Style:

Hexagon

Head Height:

Between 0.160 inches and 0.200 inches

Width Between Flats:

Between 0.684 inches and 0.692 inches

Hole Diameter:

Between 0.046 inches and 0.056 inches

First Diameter From Head:

Between 0.325 inches and 0.327 inches

Second Diameter From Head:

Between 0.432 inches and 0.436 inches

Third Diameter From Head:

Between 0.325 inches and 0.327 inches

Fourth Diameter From Head:

Between 0.432 inches and 0.436 inches

Fifth Diameter From Head:

Between 0.362 inches and 0.367 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.084 inches and 0.104 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.613 inches and 0.619 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.707 inches and 0.713 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 0.795 inches and 0.805 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

Between 0.865 inches and 0.885 inches

Thread Diameter:

0.437 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Hole Configuration Style:

Hexagon flats

Externally Relieved Body Diameter Quantity:

5

Material:

Steel comp 302 or steel comp 303

Material Specification:

Qq-s-763 federal specification single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0