NSN 5306-01-076-7202

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-076-7202



Thread Class: 3a Thread Direction: Right-hand

Thread Length:

Between 0.579 inches and 0.629 inches

Fastener Length:

Between 0.964 inches and 0.994 inches

Head Style:

Spline extended washer

Head Height:

Between 0.247 inches and 0.287 inches

Width Between Flats:

Between 0.383 inches and 0.389 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.035 inches and 0.055 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

Thread Series Designator:

Unjf

NSN 5306-01-076-7202

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

