## NSN 5306-01-076-9404

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-076-9404 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.355 inches and 0.416 inches **Fastener Length:** Between 1.865 inches and 1.906 inches **Head Style:** Hexagon **Head Height:** Between 0.151 inches and 0.171 inches Width Between Flats: Between 0.490 inches and 0.502 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5306-01-076-9404

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.