

View Online at <https://aerobasegroup.com/nsn/5306-01-077-4827>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.890 inches and 0.950 inches

**Fastener Length:**

3.330 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.388 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

0.091 inches

**Shank Unthreaded Hole Diameter:**

0.099 inches all holes and 0.114 inches all holes

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 2.380 inches and 2.440 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

40.0 rockwell c and 44.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.130 inches all holes

**Surface Finish:**

32.0 microinches head

**Special Features:**

2 holes intersecting 90 degrees apart

**Material:**

Steel comp 8740

**Material Specification:**

Ams6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams2401 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0