## NSN 5306-01-078-2346

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-078-2346

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.535 inches and 0.565 inches  |
| Fastener Length:   |
| Between 0.845 inches and 0.875 inches  |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.303 inches and 0.313 inches  |
| Head Height:   |
| Between 0.185 inches and 0.190 inches  |
| First Diameter From Head:  |
| 0.151 inches   |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:                |
| 0.310 inches   |
| Internal Drive Style:  |
| Hexagon Thread Diameter:   |
|  |
| 0.190 inches Width Across Flats:   |
| Between 0.156 inches and 0.159 inches  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Externally Relieved Body Diameter Quantity:  |
| 1  |
| Material:  |
| Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Material Specification:  |
| 66 federal standard all material responses   |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response                                |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
|  |

## NSN 5306-01-078-2346

Internal Wrenching Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

