

View Online at <https://aerobasegroup.com/nsn/5306-01-078-2919>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.803 inches and 0.853 inches

Fastener Length:

Between 2.813 inches and 2.843 inches

Head Style:

Spline extended washer

Head Height:

Between 0.291 inches and 0.331 inches

Extended Washer Diameter:

Between 0.740 inches and 0.750 inches

Extended Washer Thickness:

Between 0.072 inches and 0.092 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Head Minor Diameter:

Between 0.514 inches and 0.521 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 1.990 inches and 2.010 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Special Features:

Color white

Material:

Steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Paint top of head

Surface Treatment Specification:

Tt-e-489 no.17875 mfr ref single treatment response top of head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.